

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method for detecting signal information in a wireless relaying network, said method comprising the steps of:

[[ - ]] a first network node storing, as a priori known signal information, previously received signal information representative of a first set of information including at least one data unit to be transmitted in total more than one time over at least one link;

[[ - ]] said first network node subsequently receiving signal information representative of a second set of information, wherein a transmission of said at least one data unit by a second network node interferes with the reception of said second set of information; and

[[ - ]] said first network node detecting at least part of said second set of information by interference cancellation based on the received signal information representative of said second set of information and at least part of said previously stored a priori known signal information;

wherein said step of said first network node detecting at least part of said second set of information includes the step of processing a set  $\tilde{D}_\Sigma$  representative of previously detected data packets and the received signal information  $R_i$  according to:

$$\tilde{D} = f(R_i, \tilde{D}_\Sigma),$$

where  $f$  is a predetermined objective function and  $\tilde{D}$  is the resulting set of detected data packets.

2. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said interference cancellation includes at least one of explicit and implicit interference cancellation.
3. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said at least one data unit is to be transmitted in total more than one time over more than one link.
4. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said wireless relaying network includes at least one of a wireless multi-hop network, a cooperative relaying network and a repeater-based network.
5. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said wireless relaying network is a wireless multi-hop network.
6. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said detecting step involves one of single-user detection and multi-user detection.
7. (Canceled).

8. (Currently Amended) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said step of said first network node detecting at least part of said second set of information comprises the steps of:

[[ -]] removing a priori known signal information from the received signal information to generate a residual signal; and

[[ -]] processing said residual signal to detect at least part of said second set of information.

9. (Previously Presented) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said a priori known signal information includes previously received baseband signal information, and said step of said first network node detecting at least part of said second set of information comprises the step of jointly processing said previously received baseband signal information and subsequently received baseband signal information to detect at least part of said second set of information.

10. (Original) The method for detecting signal information in a wireless relaying network according to claim 9, wherein said previously received baseband signal information relate to a number of previous communication instances and the subsequently received baseband signal information relates to the current communication instance, and said previously received baseband signal information and said subsequently received baseband signal information are processed together with complex channel gain information to determine an estimation of at least one detected data packet.

11. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said a priori known signal information includes previously received and detected information.

12. (Original) The method for detecting signal information in a wireless relaying network according to claim 11, wherein said previously received and detected information includes previously overheard information.

13. (Previously Presented) The method for detecting signal information in a wireless relaying network according to claim 1, wherein said step of said first network node detecting at least part of said second set of information is based on transmission schedule information.

14. (Original) The method for detecting signal information in a wireless relaying network according to claim 13, wherein said first set of information includes a number of data packets, and said transmission schedule information includes information on which of the data packets that are to be transmitted when the signal information representative of said second set of information is received such that an appropriate part of said previously stored a priori known signal information is exploited in said detecting step.

15. (Original) The method for detecting signal information in a wireless relaying network according to claim 1, further comprising the step of continuously updating said a priori known signal information.

16. (Currently Amended) An arrangement for detecting signal information in a wireless relaying network, said arrangement comprising:

[[1]] means arranged in a first network node for storing, as a priori known signal information, previously received signal information representative of a first set of information, including at least one data unit to be transmitted more than one time over at least one link;

[[1]] means arranged in said first network node for receiving signal information representative of a second set of information, wherein a transmission of said at least one data unit by a second network node interferes with the reception of said second set of information; and

[[1]] means arranged in said first network node for detecting at least part of said second set of information by interference cancellation based on the received signal information representative of said second set of information and at least part of said previously stored a priori known signal information;

wherein said means for detecting at least part of said second set of information includes means for processing a set  $\tilde{D}_\Sigma$  representative of previously detected data packets and the received signal information  $R_i$  according to:

$$\underline{\tilde{D} = f(R_i, \tilde{D}_\Sigma)}$$

where  $f$  is a predetermined objective function and  $\tilde{D}$  is the resulting set of detected data packets.

17. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said interference cancellation includes at least one of explicit and implicit interference cancellation.

18. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said at least one data unit is to be transmitted in total more than one time over more than one link.

19. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said wireless relaying network includes at least one of a wireless multi-hop network, a cooperative relaying network and a repeater-based network.

20. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said wireless relaying network is a wireless multi-hop network.

21. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said means for detecting is operable for performing at least one of single-user detection and multi-user detection.

22. (Canceled).

23. (Currently Amended) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said means for detecting at least part of said second set of information comprises:

[[ -]] means for removing a priori known signal information from the received signal information to generate a residual signal; and

[[ -]] means for processing said residual signal to detect at least part of said second set of information.

24. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said a priori known signal information includes previously received baseband signal information, and said means for detecting at least part of said second set of information comprises means for jointly processing said previously received baseband signal information and the subsequently received baseband signal information to detect at least part of said second set of information.

25. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 24, wherein said previously received baseband signal information relate to a number of previous communication instances and the subsequently received baseband signal information relates to the current communication instance, and said means for jointly processing is operable for processing said previously received baseband signal information and said subsequently received baseband signal information together with complex channel gain information to determine an estimation of at least one detected data packet.

26. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said a priori known signal information includes previously received and detected information.

27. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 26, wherein said previously received and detected information includes previously overheard information.

28. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said means for detecting at least part of said second set of information operates based on transmission schedule information.

29. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 28, wherein said first set of information includes a number of data packets, and said transmission schedule information includes information on which of the data packets that are to be transmitted when the signal information representative of said second set of information is received, and said means for detecting comprises means for selecting, based on said transmission schedule information, an appropriate part of said previously stored a priori known signal information for use in detecting at least part of said second set of information.

30. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, further comprising means for continuously updating said a priori known signal information by incorporating newly detected information and removing outdated signal information.



31. (Original) The arrangement for detecting signal information in a wireless relaying network according to claim 16, wherein said arrangement is implemented in a network node of said wireless relaying network.

32. (Currently Amended) Apparatus for detecting signal information in a wireless relaying network, comprising:

memory arranged in a first network node for storing, as known signal information, previously received signal information representative of a first set of information including at least one data unit to be transmitted more than one time over a link;

a receiver arranged in the first network node for receiving signal information representative of a second set of information, wherein a transmission of the one data unit by a second network node interferes with the reception of the second set of information; and

a detector arranged in the first network node for detecting at least part of the second set of information by interference cancellation based on the received signal information representative of the second set of information and at least part of the stored known signal information;

wherein the detector includes a data processor for processing a set  $\tilde{D}_\Sigma$  representative of previously detected data packets and the received signal information  $R_i$  according to:

$$\underline{\tilde{D} = f(R_i, \tilde{D}_\Sigma)}$$

where  $f$  is a predetermined objective function and  $\tilde{D}$  is the resulting set of detected data packets.

33. (Previously Presented) The apparatus according to claim 32, wherein the detector is operable for performing at least one of single-user detection and multi-user detection.

34. (Canceled).

35. (Previously Presented) The apparatus according to claim 32, wherein the detector comprises processing circuitry for:

removing a priori known signal information from the received signal information to generate a residual signal; and

processing the residual signal to detect at least part of the second set of information.

36. (Previously Presented) The apparatus according to claim 32, wherein said known signal information includes previously received baseband signal information, and the detector is configured to jointly process previously received baseband signal information and subsequently received baseband signal information to detect at least part of the second set of information.

37. (Previously Presented) The apparatus according to claim 36, wherein the previously received baseband signal information relate to a number of previous communication instances and the subsequently received baseband signal information relates to the current communication instance, and the detector is configured to process the previously received baseband signal information and the subsequently received baseband signal information together with complex channel gain information to determine an estimation of at least one detected data packet.

38. (Previously Presented) The apparatus according to claim 32 implemented in a network node of the wireless relaying network.